

Please amend the claims as follows:

1. (Previously presented) A method for detecting the occurrence of surge or incipient surge in a centrifugal compressor, the method comprising the steps of:  
operating the centrifugal compressor having an inlet passage, an inlet passage wall and an impeller, thereby establishing a bulk fluid flow to the compressor and a local axial fluid flow in a recirculation zone in the inlet passage proximate to the inlet passage wall and proximate to the impeller; and  
detecting a decrease in the local axial fluid flow, wherein the decrease in the local fluid flow is greater than any concurrent decrease in the bulk fluid flow to the compressor.
2. (Currently amended) A method as in Claim 1 wherein the step of ~~measuring~~ detecting the local fluid flow includes detecting a reversal in the local fluid flow direction in the recirculation zone.
3. (Currently amended) A method as in Claim 1 wherein the step of ~~measuring~~ detecting the local fluid flow includes ~~measuring~~ detecting a tangential component to the local fluid flow in the recirculation zone.
4. (Currently amended) A method as in Claim 1 wherein the step of ~~measuring~~ detecting the fluid flow includes ~~measuring~~ detecting a substantial decrease in the local axial fluid flow in the recirculation zone.
5. (Currently amended) A method as in Claim 1 wherein the step of ~~measuring~~ detecting the fluid flow includes ~~measuring~~ detecting changes in the local fluid flow temperature in the recirculation zone.
6. (Currently amended) A method as in Claim 2 wherein the step of ~~measuring~~ detecting the fluid flow includes ~~measuring~~ detecting the local fluid flow temperature in the recirculation zone.

7. (Previously presented) A method as in Claim 1 further comprising the step of controlling the bulk fluid flow through the compressor.

8. (Previously presented) A method as in Claim 7 wherein the step of controlling the fluid flow includes increasing the bulk fluid flow to the inlet passage.

9. (Previously presented) A method as in Claim 2 further comprising the step of controlling the bulk fluid flow through the compressor.

10. (Previously presented) A method as in Claim 3 further comprising the step of controlling the bulk fluid flow through the compressor.

11. (Previously presented) A method as in Claim 5 further comprising the step of controlling the bulk fluid flow through the compressor.

12. (Previously presented) A method as in Claim 4 further comprising the step of controlling the bulk fluid flow through the compressor.

13. (Previously presented) A method as in Claim 1 wherein the step of detecting includes measuring the fluid flow using at least one fluid velocity sensor.

14. (Original) A method as in Claim 13 wherein the at least one fluid velocity sensor is attached to the inlet passage wall.

15. (Currently amended) A method of detecting surge or incipient surge in a centrifugal compressor, the compressor having an impeller and an inlet passage upstream of the impeller, the method comprising the steps of:

operating the compressor, thereby establishing a substantially steady state fluid flow through the inlet passage and impeller; and

measuring the local fluid flow velocity in a recirculation zone in the inlet passage proximate to the inlet passage wall and proximate to the impeller; wherein the step of measuring the fluid flow includes measuring a tangential component to the fluid flow in the recirculation zone.

16. (Previously presented) A method as in Claim 15 wherein the step of measuring the fluid flow includes detecting a reversal in the fluid flow direction in the recirculation zone.

17. (Canceled)

18. (Previously presented) A method as in Claim 15 wherein the step of measuring the fluid flow includes measuring a substantial decrease in the axial fluid flow in the recirculation zone.

19. (Original) A method as in Claim 15 wherein the step of measuring the fluid flow includes measuring changes in the fluid flow temperature.

20. (Original) A method as in Claim 16 wherein the step of measuring the fluid flow includes measuring changes in the fluid flow temperature.

21. (Original) A method as in Claim 15 further comprising the step of controlling the flow through the compressor.

22. (Original) A method as in Claim 21 wherein the step of controlling the fluid flow includes increasing the fluid flow to the inlet passage.

23. (Original) A method as in Claim 16 further comprising the step of controlling the flow through the compressor.

24. (Original) A method as in Claim 20 further comprising the step of controlling the flow through the compressor.

25. (Original) A method as in Claim 21 further comprising the step of controlling the flow through the compressor.

26. (Original) A method as in Claim 15 wherein the step of measuring includes measuring the fluid flow using at least one fluid velocity sensor.

27. (Original) A method as in Claim 26, the inlet passage having an inlet passage wall and wherein the at least one fluid velocity sensor is attached to the inlet passage wall.

28. (Currently amended) A method for detecting the occurrence of surge or incipient surge in a fluid flow system, the fluid flow system having a centrifugal compressor in fluid communication with an upstream fluid conduit and a downstream fluid conduit, the centrifugal compressor having an inlet passage and an impeller, the method comprising the steps of:

operating the compressor, thereby establishing substantially steady state fluid flow through the inlet passage and impeller; and

measuring the fluid flow in a recirculation zone in the inlet passage proximate to the inlet passage wall and proximate to the impeller, wherein the step of measuring the fluid flow includes measuring a tangential component to the fluid flow in the recirculation zone.

29. (Previously presented) A method as in Claim 28 wherein the step of measuring the fluid flow includes measuring a reverse in the fluid flow direction in the recirculation zone.

30. (Canceled)

31. (Previously presented) A method as in Claim 28 wherein the step of measuring the fluid flow includes measuring a substantial decrease in the axial fluid flow in the recirculation zone.

32. (Original) A method as in Claim 28 wherein the step of measuring the fluid flow includes measuring changes in the fluid flow temperature.

33. (Original) A method as in Claim 28 further comprising the step of controlling the flow through the compressor.

34. (Original) A method as in Claim 33 wherein the step of controlling the fluid flow includes increasing the fluid flow to the inlet passage.

35. (Original) A method as in Claim 29 further comprising the step of controlling the flow through the compressor.

36. (Canceled)

37. (Original) A method as in Claim 31 further comprising the step of controlling the flow through the compressor.

38. (Original) A method as in Claim 32 further comprising the step of controlling the flow through the compressor.

39. (Original) A method as in Claim 28 wherein the step of measuring includes measuring the fluid flow using at least one fluid velocity sensor.

40. (Original) A method as in Claim 39, the inlet passage having an inlet passage wall and wherein the at least one fluid velocity sensor is attached to the inlet passage wall.

41. (Original) A method as in Claim 28 wherein the fluid flow system comprises a gas pipeline.

42. (Original) A method as in Claim 29 wherein the step of measuring includes measuring changes in the fluid temperature.

43. (Currently amended) An apparatus for detecting the occurrence of surge or incipient surge in a centrifugal compressor, the apparatus comprising:

a centrifugal compressor having an inlet passage, with an inlet passage wall, and an impeller, a zone defined proximate the wall of the inlet passage and proximate the impeller, immediately upstream of the impeller; and

at least one sensor operable for measuring fluid flow in said zone, wherein the sensor is capable of measuring a tangential component of fluid flow in the zone.

44. (Previously presented) An apparatus as in Claim 43 wherein at least one sensor is a fluid velocity sensor measuring fluid flow speed and direction.

45. (Previously presented) An apparatus as in Claim 43 wherein at least one sensor is capable of measuring a reversal in fluid flow direction in the zone.

46. (Canceled)

47. (Previously presented) An apparatus as in Claim 43 further comprising a temperature sensor.

48. (Previously presented) An apparatus as in Claim 44 further comprising a temperature sensor.

49. (Original) An apparatus as in Claim 43 wherein the at least one sensor is attached to the inlet passage wall.

50. (Original) An apparatus as in Claim 43 further comprising a means of controlling the fluid flow through the centrifugal compressor.

51. (Original) An apparatus as in Claim 44 further comprising a means of controlling the fluid flow through the centrifugal compressor.

52. (Original) An apparatus as in Claim 45 further comprising a means of controlling the fluid flow through the centrifugal compressor.

53. (Canceled)